

west virginia department of environmental protection

Office of Oil and Gas 601 57th Street SE Charleston, WV 25304 (304) 926-0450 (304) 926-0452 fax Earl Ray Tomblin, Governor Randy C. Huffman, Cabinet Secretary www.dep.wv.gov

December 30, 2013

WELL WORK PERMIT

Horizontal 6A Well

This permit, API Well Number: 47-1706398, issued to ANTERO RESOURCES CORPORATION, is evidence of permission granted to perform the specified well work at the location described on the attached pages and located on the attached plat, subject to the provisions of Chapter 22 of the West Virginia Code of 1931, as amended, and all rules and regulations promulgated thereunder, and to all conditions and provisions outlined in the pages attached hereto. Notification shall be given by the operator to the Oil and Gas Inspector at least 24 hours prior to the construction of roads, locations, and/or pits for any permitted work. In addition, the well operator shall notify the same inspector 24 hours before any actual well work is commenced and prior to running and cementing casing. Spills or emergency discharges must be promptly reported by the operator to 1-800-642-3074 and to the Oil and Gas inspector.

Please be advised that form WR-35, Well Operators Report of Well Work is to be submitted to this office within 90 days completion of permitted well work, as should form WR-34 Discharge Monitoring Report within 30 days of discharge of pits, if applicable. Failure to abide by all statutory and regulatory provisions governing all duties and operations hereunder may result in suspension or revocation of this permit and, in addition, may result in civil and/or criminal penalties being imposed upon the operators.

In addition to the applicable requirements of this permit, and the statutes and rules governing oil and gas activity in WV, this permit may contain specific conditions which must be followed. Permit conditions are attached to this cover letter.

Per 35CSR-4-5.2.g this permit will expire in two (2) years from the issue date unless permitted well work is commenced. If there are any questions, please feel free to contact me at (304) 926-0499 ext. 1654.

James Martin

Chief

Operator's Well No: MCMILLIAN UNIT 2H

Farm Name: TRUSTEES CHESTNUT GROVE (

API Well Number: 47-1706398

Permit Type: Horizontal 6A Well

Date Issued: 12/30/2013

Promoting a healthy environment.

API Number: 39/285;:

PERMIT CONDITIONS

West Virginia Code § 22-6A-8(d) allows the Office of Oil and Gas to place specific conditions upon this permit. Permit conditions have the same effect as law. <u>Failure to adhere to the specified permit</u> conditions may result in enforcement action.

CONDITIONS

- 1. This proposed activity may require permit coverage from the United States Army Corps of Engineers (USACOE). Through this permit, you are hereby being advised to consult with USACOE regarding this proposed activity.
- 2. If the operator encounters an unanticipated void, or an anticipated void at an unanticipated depth, the operator shall notify the inspector within 24 hours. Modifications to the casing program may be necessary to comply with W. Va. Code § 22-6A-5a (12), which requires drilling to a minimum depth of thirty feet below the bottom of the void, and installing a minimum of twenty (20) feet of casing. Under no circumstance should the operator drill more than fifty (50) feet below the bottom of the void or install less than twenty (20) feet of casing below the bottom of the void.
- 3. When compacting fills, each lift before compaction shall not be more than 12 inches in height, and the moisture content of the fill material shall be within limits as determined by the Standard Proctor Density test of the actual soils used in specific engineered fill, ASTM D698, Standard Test Method for Laboratory Compaction Characteristics of Soil Using Standard Effort, to achieve 95 % compaction of the optimum density. Each lift shall be tested for compaction, with a minimum of two tests per lift per acre of fill. All test results shall be maintained on site and available for review.
- 4. Operator shall install signage per § 22-6A-8g (6) (B) at all source water locations included in their approved water management plan within 24 hours of water management plan activation.
- 5. Oil and gas water supply wells will be registered with the Office of Oil and Gas and all such wells will be constructed and plugged in accordance with the standards of the Bureau for Public Health set forth in its Legislative rule entitled *Water Well Regulations*, 64 C.S.R. 19. Operator is to contact the Bureau of Public Health regarding permit requirements. In lieu of plugging, the operator may transfer the well to the surface owner upon agreement of the parties. All drinking water wells within fifteen hundred feet of the water supply well shall be flow tested by the operator upon request of the drinking well owner prior to operating the water supply well.
- 6. Pursuant to the requirements pertaining to the sampling of domestic water supply wells/springs the operator shall, no later than thirty (30) days after receipt of analytical data provide a written copy to the Chief and any of the users who may have requested such analyses.
- 7. If any explosion or other accident causing loss of life or serious personal injury occurs in or about a well or well work on a well, the well operator or its contractor shall give notice, stating the particulars of the explosion or accident, to the oil and gas inspector and the Chief, within 24 hours of said accident.
- 8. During the casing and cementing process, in the event cement does not return to the surface, the oil and gas inspector shall be notified within 24 hours.



Applicant: Antero Resources Corporation Reference ID: McMillan Unit 2H (Chestnut Pad) (09/26/2013)

Status: New

Type: Horizontal 6A Well Permit ID: New/Pending Printed: Dec. 30, 2013

12:42 PM

WW-6B: General and Location Information

ww-6B: General and Location	intermation
API Number:	47-017-06398 (47)
Operator's Well Number:	McMillan Unit 2H
Filing Fee:	○ First Well on Pad
Well Pad Name:	Chestnut Pad
Surface Owner:	Trustees of Chestnut Grove Church
Public Road Access:	CR 14
Please attach each of the followi Well Plat Wellbore Schematic	ng as seperate documents:
County: Doddridge	District: West Union ▼
Quadrangle: SMITHBURG	G ▼
Top Hole(UTM NAD83):	7 47
Easting: 524017	Northing: 4357129 Zone: 17 <u>▼</u>
Proposed Landing Point(UTM):	
Easting: 524396	Northing: 4357393 Zone: 17 ▼
Proposed Bottom Hole(UTM):	
Easting: 525544	Northing: 4354552 Zone: 17 ▼
Elevations (feet) Current Gro	und: 1155 Proposed Post-Construction: 1115
Well Type: Gas	○ Oil
	ound Storage C Other
Will well be drilled more than 100) feet into the Onondaga Group? O Yes O No
Depth Type:	C Deep
Existing Pad?	No

Target Formations

Complete the following table.			
Target Formation	Depth-Top (ft)	Anticipated Thickness (ft)	Associated Pressure (psi)
Marcellus Shale	7200	55	2950

Depth Specifics

Proposed Post-Construction Elevation:	1377
Proposed Total Vertical Depth:	7200 (ft.)
Formation at Total Vertical Depth:	Marcellus Shale
Proposed Total Measured Depth:	19500 (ft.)
Proposed Total Horizontal Leg Length:	10056 (ft.)
Method to Determine Fresh Water Depth:	
Offset well records. Depths has surface elevations.	ve been adjusted according to
	-

		Approximate Fresh Water Strata Depths	
222	(ft.)		
249	(ft.)		

		Approximate Coal Seam Depths
295	(ft.)	Coal Seam Name, if known:
812	(ft.)	Coal Seam Name, if known:
1122	(ft.)	Coal Seam Name, if known:

	Approximate Depth to Possible Void(coal mine, karst, other)	
(ft.)	Not Anticipated:	

Approximate Saltwater Depths	
1020 (ft.)	
1514 (ft.)	

Well Work and Mine Details

Is proposed well location directly overlying or tributary to an	active mine?	
C Yes • No		
If Yes, indicate name, depth, coal seam and owner of mine:		
Coal Seam:	Depth:	
Mine Name:	Owner:	
Describe proposed well work, including the drilling and plug	ging back of any pilot hole.	
Drill, perforate, fracture a new horizon	ntal shallow well and	A.
complete Marcellus Shale.		
Describe fracturing/stimulating methods in detail, including a	inticipated max pressure and anticipa	ated max rate.
Antero plans to pump Slickwater into the formation in order to ready the well fowill be comprised of approximately 99 pwith less than 1 percent special-purpose the attached "List of Anticipated Addit or Stimulating Well."	r production. The fluid ercent water and sand, e additives as shown in	*
Total area to be disturbed, including roads, stockpile area, p Area to be disturbed for well pad only, less access road (acr		
Thea to be distribed for well pad only, less access load (act	60 <i>)</i> . 2.00	

Casing and Cementing

Complete the following table, adding as many rows of each Type as needed.										
Туре	Size (in) New or Used		Grade		Weight per ft. (lb/ft)		Footage: For I		Intervals: Left in Well	
Conductor	20"	New	H-4	10	94#	40	10			
	Wellbore Diameter (in)			Wall Ti	hickness (in)		Burst Pre	ssure	(psi)	
	24"			0.438"		153	30			
	Cement Type			d (cu. ft./sk)	Fillup - Cubic	Feet Top of Cement			rculated to Surface?	
	Class A		1.18		38		0		V	
	Size (in) New or Used		Grade							
Туре	Size (in)			Grade	Weight per ft. (lb/ft)		age: For rilling		als: Left in Well	
Type Fresh Water	Size (in)		J-5	Grade 5/H-40						
	` '	Used New	J-5	5/H-40	(lb/ft)	D		305		
	13-3/8"	Used New	J-5	5/H-40	(lb/ft) 54.5#/48#	D	rilling Burst Pre	305	Well	
	13-3/8" Wellbore Dia	Used New ameter (in)		5/H-40 Wall Ti	(lb/ft) 54.5#/48#	305 273	rilling Burst Pre	305 ssure	Well	
	13-3/8" Wellbore Dia	Used New ameter (in)		5/H-40 Wall TI	(lb/ft) 54.5#/48# hickness (in)	305 273	Burst Pre Top of	305 ssure	(psi)	

Туре	Size (in)	New or Used		Grade	Weight per ft. (lb/ft)		age: For rilling	Intervals: Left in Well	
Coal	9-5/8"	New	J-55		36#	2460	460 2460		
	Wellbore Dia	ameter (in)	Wall Ti		hickness (in)		Burst Pre	ssure (psi)	
	12-1/4"			0.352"		3520			
	Cement Type		Yield (cu. ft./sk)		Fillup - Cubic	Fillup - Cubic Feet		Circulated to Surface?	
	Class A		1.18		1002		0	~	
Туре	Size (in)	New or Used	Grade		Weight per ft. (lb/ft)		age: For rilling	Intervals: Left in Well	
Production _	5-1/2"	New	P-1	10	20#	20# 19500		19500	
	Wellbore Dia	ameter (in)		Wall Ti	hickness (in)	Burst Pressure (psi)			
	8.75"/8.5"		0.361"			12630			
	Cement Ty	ре	Yield (cu. ft./sk)		Fillup - Cubic	Feet Top of Cement			
	Lead-H/POZ & Ta	il - H	H/PC	Z-1.44	4967	1960			
Туре	Size (in)	New or Used		Grade	Weight per ft. (lb/ft)			Intervals: Left in Well	
Tubing	2-3/8"	New	N-8	30	4.7#	N/A		7100	
	Wellbore Dia	ameter (in)		Wall Ti	hickness (in)	Burst Pressur		ssure (psi)	
	4.778"			0.19"		112	200		
	Cement Ty	ре	Yiel	d (cu. ft./sk)	Fillup - Cubic	Fillup - Cubic Feet		Circulated to Surface?	
	N/A		N/A		N/A		N/A		

Packers

Will Packers be Used?	C Yes	No	
If Yes, complete	he followin	g:	

Kind	Sizes	Depths Set

Fluids, Cuttings Disposal and Reclamation Plan

State:	West Virginia		County:	<u>Doddridge</u>
District:	<u>017</u>		Quadrangle:	: <u>SMITHBURG</u>
Zone:	<u>17</u>			
Northing:	4357129		Easting:	<u>524017</u>
ĺ				
API Numb	ber:	<u>47-017-06398</u>		
Operator	Well Number:	McMillan Unit 2H		
Do you a	inticipate drilling/red	drilling well work?		
(• Yes C No)		
ĺ				
Will a pit	be used for pluggir	ng activities?	No	

nthetic liner be used in the pit? C Yes No	
f so, what ml.? N/A	
d Disposal Method For Treated Pit Waste Water:	
Underground Injection (UIC Permit Number	
Reuse (at API Number	
WR-34	
Other (explain)	
Other (explain)	
ed loop system be used?	
f so, describe:	
*Drilling and Flowback fluids will be stored in tanks.	
Cuttings will be tanked and hauled off site.	
1. Steel mud pits as part of the rig equipment for cleaning and	
conditioning the mud prior to being pumped down hole 2. Half	
rounds under the shale shakers for capturing cuttings and an	
auger for transporting cuttings from the half round to the	
auger for transporting cuttings from the half round to the cuttings boxes that are used to haul the cuttings to an	
auger for transporting cuttings from the half round to the	
auger for transporting cuttings from the half round to the cuttings boxes that are used to haul the cuttings to an approved offsite disposal facility 3. Frac tanks for any excess capacity mud storage that is required bayound the rig's steel pits 4. A flow line that transports the mud from the wellbore	
auger for transporting cuttings from the half round to the cuttings boxes that are used to haul the cuttings to an approved offsite disposal facility 3. Frac tanks for any excess capacity mud storage that is required bayound the rig's steel pits 4. A flow line that transports the mud from the wellbore to the steel pits for cleaning and conditioning 5. Hose lines	
auger for transporting cuttings from the half round to the cuttings boxes that are used to haul the cuttings to an approved offsite disposal facility 3. Frac tanks for any excess capacity mud storage that is required bayound the rig's steel pits 4. A flow line that transports the mud from the wellbore to the steel pits for cleaning and conditioning 5. Hose lines running from the steel mud pits to the mud pumps and from the	
auger for transporting cuttings from the half round to the cuttings boxes that are used to haul the cuttings to an approved offsite disposal facility 3. Frac tanks for any excess capacity mud storage that is required bayound the rig's steel pits 4. A flow line that transports the mud from the wellbore to the steel pits for cleaning and conditioning 5. Hose lines	
auger for transporting cuttings from the half round to the cuttings boxes that are used to haul the cuttings to an approved offsite disposal facility 3. Frac tanks for any excess capacity mud storage that is required bayound the rig's steel pits 4. A flow line that transports the mud from the wellbore to the steel pits for cleaning and conditioning 5. Hose lines running from the steel mud pits to the mud pumps and from the mud pumps to the top drive for transporting the mud to the	
auger for transporting cuttings from the half round to the cuttings boxes that are used to haul the cuttings to an approved offsite disposal facility 3. Frac tanks for any excess capacity mud storage that is required bayound the rig's steel pits 4. A flow line that transports the mud from the wellbore to the steel pits for cleaning and conditioning 5. Hose lines running from the steel mud pits to the mud pumps and from the mud pumps to the top drive for transporting the mud to the drill pipe to be sent down hole Please Note: We DO NOT use an earthen reserve pit. Not using an earthen reserve pit is generally considered to be the	
auger for transporting cuttings from the half round to the cuttings boxes that are used to haul the cuttings to an approved offsite disposal facility 3. Frac tanks for any excess capacity mud storage that is required bayound the rig's steel pits 4. A flow line that transports the mud from the wellbore to the steel pits for cleaning and conditioning 5. Hose lines running from the steel mud pits to the mud pumps and from the mud pumps to the top drive for transporting the mud to the drill pipe to be sent down hole Please Note: We DO NOT use an earthen reserve pit. Not using an	
auger for transporting cuttings from the half round to the cuttings boxes that are used to haul the cuttings to an approved offsite disposal facility 3. Frac tanks for any excess capacity mud storage that is required bayound the rig's steel pits 4. A flow line that transports the mud from the wellbore to the steel pits for cleaning and conditioning 5. Hose lines running from the steel mud pits to the mud pumps and from the mud pumps to the top drive for transporting the mud to the drill pipe to be sent down hole Please Note: We DO NOT use an earthen reserve pit. Not using an earthen reserve pit is generally considered to be the	_
auger for transporting cuttings from the half round to the cuttings boxes that are used to haul the cuttings to an approved offsite disposal facility 3. Frac tanks for any excess capacity mud storage that is required bayound the rig's steel pits 4. A flow line that transports the mud from the wellbore to the steel pits for cleaning and conditioning 5. Hose lines running from the steel mud pits to the mud pumps and from the mud pumps to the top drive for transporting the mud to the drill pipe to be sent down hole Please Note: We DO NOT use an earthen reserve pit. Not using an earthen reserve pit is generally considered to be the	*
auger for transporting cuttings from the half round to the cuttings boxes that are used to haul the cuttings to an approved offsite disposal facility 3. Frac tanks for any excess capacity mud storage that is required bayound the rig's steel pits 4. A flow line that transports the mud from the wellbore to the steel pits for cleaning and conditioning 5. Hose lines running from the steel mud pits to the mud pumps and from the mud pumps to the top drive for transporting the mud to the drill pipe to be sent down hole Please Note: We DO NOT use an earthen reserve pit. Not using an earthen reserve pit is generally considered to be the	V
auger for transporting cuttings from the half round to the cuttings boxes that are used to haul the cuttings to an approved offsite disposal facility 3. Frac tanks for any excess capacity mud storage that is required bayound the rig's steel pits 4. A flow line that transports the mud from the wellbore to the steel pits for cleaning and conditioning 5. Hose lines running from the steel mud pits to the mud pumps and from the mud pumps to the top drive for transporting the mud to the drill pipe to be sent down hole Please Note: We DO NOT use an earthen reserve pit. Not using an earthen reserve pit is generally considered to be the definition of a "closed loop" mud system. Medium anticipated for this well (vertical and horizontal)? Air, freshwater, oil based, etc. Surface - Air/Freshwater, Intermediate - Dust/Stiff Foam,	Ψ.
auger for transporting cuttings from the half round to the cuttings boxes that are used to haul the cuttings to an approved offsite disposal facility 3. Frac tanks for any excess capacity mud storage that is required bayound the rig's steel pits 4. A flow line that transports the mud from the wellbore to the steel pits for cleaning and conditioning 5. Hose lines running from the steel mud pits to the mud pumps and from the mud pumps to the top drive for transporting the mud to the drill pipe to be sent down hole Please Note: We DO NOT use an earthen reserve pit. Not using an earthen reserve pit is generally considered to be the definition of a "closed loop" mud system.	¥
auger for transporting cuttings from the half round to the cuttings boxes that are used to haul the cuttings to an approved offsite disposal facility 3. Frac tanks for any excess capacity mud storage that is required bayound the rig's steel pits 4. A flow line that transports the mud from the wellbore to the steel pits for cleaning and conditioning 5. Hose lines running from the steel mud pits to the mud pumps and from the mud pumps to the top drive for transporting the mud to the drill pipe to be sent down hole Please Note: We DO NOT use an earthen reserve pit. Not using an earthen reserve pit is generally considered to be the definition of a "closed loop" mud system. Medium anticipated for this well (vertical and horizontal)? Air, freshwater, oil based, etc. Surface - Air/Freshwater, Intermediate - Dust/Stiff Foam,	¥
auger for transporting cuttings from the half round to the cuttings boxes that are used to haul the cuttings to an approved offsite disposal facility 3. Frac tanks for any excess capacity mud storage that is required bayound the rig's steel pits 4. A flow line that transports the mud from the wellbore to the steel pits for cleaning and conditioning 5. Hose lines running from the steel mud pits to the mud pumps and from the mud pumps to the top drive for transporting the mud to the drill pipe to be sent down hole Please Note: We DO NOT use an earthen reserve pit. Not using an earthen reserve pit is generally considered to be the definition of a "closed loop" mud system. Medium anticipated for this well (vertical and horizontal)? Air, freshwater, oil based, etc. Surface - Air/Freshwater, Intermediate - Dust/Stiff Foam,	¥ ¥
Ruger for transporting cuttings from the half round to the cuttings boxes that are used to haul the cuttings to an approved offsite disposal facility 3. Frac tanks for any excess capacity mud storage that is required bayound the rig's steel bits 4. A flow line that transports the mud from the wellbore to the steel pits for cleaning and conditioning 5. Hose lines running from the steel mud pits to the mud pumps and from the mud pumps to the top drive for transporting the mud to the drill pipe to be sent down hole Please Note: We DO NOT use an earthen reserve pit. Not using an earthen reserve pit is generally considered to be the definition of a "closed loop" mud system. Redium anticipated for this well (vertical and horizontal)? Air, freshwater, oil based, etc. Production - Water Based Mud	¥ ¥

Additives to be used in drilling medium?	
Please See Attachment	*
Drill cuttings disposal method?	
Leave in Pit (medium used) N/A Explain:	
Landfill (name/permit number?)	
Removed Offsite (name/permit number?) Meadowfill Landfill(Permit #SWF-1032-98)	
Other: (please explain)	

	Propose	ed Revegetation Treatment:		
Acres Disturbed:	17.91	Prevegetation pH:	N/A	
Lime Tons/acre to c	correct to pH: 2-4			
Fertilizer (10-20-20	or equivalent): 500	lbs/acre		
Mulch	2-3 lbs/acre			
Comments:	Hay or straw or Wood	Fiber (will be used whe	ere needed)	*
	1	ccess Roads to Pads (3.9 & Auxiliary Pad (11.24)		
				∇

	Seed Mixtures	
Area Type	Seed Type	lbs/acre
Temporary 🔻	Tall Fescue	45
Temporary 💌	Perennial Rye Grass	20
Permanent 🔻	Tall Fescue	45
Permanent <u></u>	Perennial Rye Grass	20

19) Describe proposed well work, including the drilling and plugging back of any pilot hole:
Drill, perforate, fracture a new horizontal shallow well and complete Marcellus Shale.
20) Describe fracturing/stimulating methods in detail, including anticipated max pressure and max rate:
Antero plans to pump Slickwater into the Marcellus Shale formation in order to ready the well for production. The fluid will be comprised of approximately 99 percent water and sand, with less than 1 percent special-purpose additives as shown in the attached "List of Anticipated Additives Used for Fracturing or Stimulating Well."
the attached List of Anticipated Additives Osed for Fracturing of Stimulating Well.
17.04
21) Total Area to be disturbed, including roads, stockpile area, pits, etc., (acres): 17.91 acres
22) Area to be disturbed for well pad only, less access road (acres): 2.69 acres
22) Thea to be distarbed for well pad only, less access road (acres).
23) Describe centralizer placement for each casing string:
Conductor: no centralizers Surface Casing: one centralizer 10' above the float shoe, one on the insert float collar and one every 4th joint spaced up the hole
to surface.
Intermediate Casing: one centralizer above float joint, one centralizer 5' above float collar and one every 4th collar to surface. Production Casing: one centralizer at shoe joint and one every 3 joints to top of cement in intermediate casing.
The state of the s
24) Describe all cement additives associated with each cement type:

Conductor: no additives, Class A cement.

Surface: Class A cement with 2-3% calcium chloride

Intermediate: Class A cement with 1/4 lb of flake, 5 gallons of clay treat

Production: Lead cement- 50/50 Class H/Poz + 1.5% salt + 1% C-45 + 0.5% C-16a + 0.2% C-12 + 0.45% C-20 + 0.05% C-51 Production: Tail cement- Class H + 45 PPS Calcium Carbonate + 1.0% FL-160 + 0.2% ACGB-47 + 0.05% ACSA-51 + 0.2% ACR-20

25) Proposed borehole conditioning procedures:

Conductor: blowhole clean with air, run casing, 10 bbls fresh water.

Surface: blowhole clean with air, trip to conductor shoe, trip to bottom, blowhole clean with air, trip out, run casing, circulate pipe capacity + 40 bbls fresh water followed by 25 bbls bentonite mud, 10 bbls fresh water spacer.

Intermediate: blowhole clean with air, trip to surface casing shoe, trip to bottom, blowhole clean with air, trip out, run casing, circulate 40 bbls brine water followed by 10 bbls fresh water and 25 bbls bentonite mud, pump 10 bbls fresh water.

Production: circulate with 14 lb/gal NaCl mud, trip to middle of lateral, circulate, pump high viscosity sweep, trip to base of curve, pump high viscosity sweep, trip to top of curve, trip to bottom, circulate, pump high viscosity sweep, trip out, run casing, circulate 10 bbls fresh water, pump 48 bbls barite pill, pump 10 bbls fresh water followed by 48 bbls mud flush and 10 bbls water.

*Note: Attach additional sheets as needed.

Form WW-9 Additives Attachment

SURFACE INTERVAL

- 1. Fresh Water
- 2. Soap –Foamer AC
- 3. Air

INTERMEDIATE INTERVAL

STIFF FOAM RECIPE:

- 1) 1 ppb Soda Ash / Sodium Carbonate-Alkalinity Control Agent
- 2) 1 ppb Conqor 404 (11.76 ppg) / Corrosion Inhibitor
- 3) 4 ppb KLA-Gard (9.17 ppg) / Amine Acid Complex-Shale Stabilizer
- 4) 1ppb Mil Pac R / Sodium Carboxymethylcellulose-Filtration Control Agent
- 5) 12 ppb KCL / Potassium Chloride-inorganic Salt
- 6) Fresh Water 80 bbls
- 7) Air

PRODUCTION INTERVAL

1. Alpha 1655

Salt Inhibitor

2. Mil-Carb

Calcium Carbonate

3. Cottonseed Hulls

Cellulose-Cottonseed Pellets – LCM

Mil-Seal

Vegetable, Cotton & Cellulose-Based Fiber Blend – LCM

5. Clay-Trol

Amine Acid Complex – Shale Stabilizer

6. Xan-Plex

Viscosifier For Water Based Muds

7. Mil-Pac (All Grades)

Sodium Carboxymethylcellulose - Filtration Control Agent

8. New Drill

Anionic Polyacrylamide Copolymer Emulsion - Shale Stabilizer

9. Caustic Soda

Sodium Hydroxide – Alkalinity Control

10. Mil-Lime

Calcium Hydroxide – Lime

11. LD-9

Polyether Polyol – Drilling Fluid Defoamer

12. Mil Mica

Hydro-Biotite Mica – LCM

13. Escaid 110

Drilling Fluild Solvent – Aliphatic Hydrocarbon

14. Ligco

Highly Oxidized Leonardite - Filteration Control Agent

15. Super Sweep

Polypropylene – Hole Cleaning Agent

16. Sulfatrol K

Drilling Fluid Additive – Sulfonated Asphalt Residuum

17. Sodium Chloride, Anhydrous

Inorganic Salt

18. D-D

Drilling Detergent – Surfactant

19. Terra-Rate

Organic Surfactant Blend

20. W.O. Defoam

Alcohol-Based Defoamer

21. Perma-Lose HT

Fluid Loss Reducer For Water-Based Muds

22. Xan-Plex D

Polysaccharide Polymer – Drilling Fluid Viscosifier

23. Walnut Shells

Ground Cellulosic Material – Ground Walnut Shells – LCM

24. Mil-Graphite

Natural Graphite – LCM

25. Mil Bar

Barite – Weighting Agent

26. X-Cide 102

Biocide

27. Soda Ash

Sodium Carbonate – Alkalinity Control Agent

28. Clay Trol

Amine Acid complex – Shale Stabilizer

29. Sulfatrol

Sulfonated Asphalt – Shale Control Additive

30. Xanvis

Viscosifier For Water-Based Muds

31. Milstarch

Starch – Fluid Loss Reducer For Water Based Muds

32. Mil-Lube

Drilling Fluid Lubricant



Well Site Safety Plan Antero Resources

Well Name: Mishka Unit 1H, McMillan Unit 1H and 2H,

Hoskinson Unit 1H and 2H

Pad Location: CHESTNUT PAD

Doddridge County/ Grant District

GPS Coordinates: Lat 39°21′47.85″/Long 80°43′16.23″ (NAD83)

Driving Directions:

west virginia department of environmental protection



Water Management Plan: Primary Water Sources



WMP-01572

API/ID Number:

047-017-06398

Operator:

Antero Resources

McMillan Unit 2H

Important:

For each proposed primary water source (including source intakes for purchased water sources) identified in your water management plan, and summarized herein, DEP has made an evaluation concerning water availability over the specified date range. DEP's assessment is based on the following considerations:

- •Statistical analysis of historical USGS stream gauge data (transferred to un-gauged locations as necessary);
- Identification of sensitive aquatic life (endangered species, mussels, etc.);
- Quantification of known existing demands on the water supply (Large Quantity Users);
- Minimum flows required by the Army Corps of Engineers; and
- ·Designated stream uses.

Based on these factors, DEP has provided, for each intake location (and origination point for purchased water), a reference gauge location and discharge flow reading which must be surpassed prior to withdrawals. Additionally, DEP has established a minimum passby flow at the withdrawal location which must also be surpassed prior to withdrawals. These thresholds are considered terms of the permit and are enforceable as such.

DEP is aware that some intake points will be used for mutiple wells and well sites. In these cases, the thresholds set by the Water Management Plan are to be interepreted as total withdrawal limits for each location over the specified date range regardless of how many wells are supported by that intake.

For all purchased water intakes, determinations of water availability are made at the original source intake location. It is the responsibility of the Oil and Gas Operator, not the seller, to cease withdrawal of water from the seller when flows are less than the minimum gauge reading at the stream gauge referenced by the Water Management Plan in order to protect stream uses.

Note that the determinations made herein are based on the best available data, but it is impossible to predict water availability in the future. While the DEP has carefully established these minimum withdrawal thresholds, it remains the operator's responsibility to protect aquatic life at all times. Approval to withdrawal is contingent upon permission from the land owner. It is the responsibility of the operator to secure and maintain permission prior to any withdrawals.

The operator is reminded that 24-48 hours prior to withdrawing (or purchasing) water, DEP must be notified by email at DEP.water.use@wv.gov.

APPROVED DEC 3 0 2013

Source Summary

WMP-01572

API Number:

047-017-06398

Operator:

Antero Resources

McMillan Unit 2H

Stream/River

 Source Ohio River @ Ben's Run Withdrawal Site

Tyler

Owners

Ben's Run Land Company

Limited Partnership

Start Date

End Date

Total Volume (gal)

Max. daily purchase (gal)

Intake Latitude: Intake Longitude:

6/23/2014

6/23/2015

8,410,000

39.46593

-81.110781

Regulated Stream?

Ohio River Min. Flow Ref. Gauge ID:

9999999

Ohio River Station: Willow Island Lock & Dam

Max. Pump rate (gpm):

3,360

Min. Gauge Reading (cfs):

6,468.00

Min. Passby (cfs)

DEP Comments:

Refer to the specified station on the National Weather Service's Ohio River forecast website: http://www.erh.noaa.gov/ohrfc//flows.shtml

West Fork River @ JCP Withdrawal

Harrison

Owner:

James & Brenda Raines

Start Date

Source

End Date

Total Volume (gal)

Max. daily purchase (gal)

Intake Latitude: Intake Longitude: 39.320913

-80.337572

6/23/2014

6/23/2015

8,410,000

3061000

WEST FORK RIVER AT ENTERPRISE, WV

Max. Pump rate (gpm):

2,000

▼ Regulated Stream? Stonewall Jackson Dam Ref. Gauge ID:

Min. Gauge Reading (cfs):

175.00

Min. Passby (cfs)

146.25

DEP Comments:

Source

West Fork River @ McDonald Withdrawal

Harrison

Owner:

David Shrieves

Start Date

End Date

Total Volume (gal)

Max. daily purchase (gal)

Intake Latitude: Intake Longitude:

6/23/2014

6/23/2015

8,410,000

39.16761

-80.45069

Regulated Stream? Stonewall Jackson Dam Ref. Gauge ID:

3061000

WEST FORK RIVER AT ENTERPRISE, WV

Max. Pump rate (gpm):

3,000

Min. Gauge Reading (cfs):

175.00

Min. Passby (cfs)

106.30

DEP Comments:

Source	West Fork Rive	er @ GAL With	drawal		Harrison	Owner:	David Shrieves
Start Date 6/23/2014	End Date 6/23/2015	Т	otal Volume (gal) 8,410,000	Max. daily pu	ırchase (gal)	Intake Latitude: 39.16422	Intake Longitude: -80.45173
Regulated	Stream? Stone	ewall Jackson	Dam Ref. Gauge ID): 306100	0	WEST FORK RIVER AT ENTE	RPRISE, WV
Max. Pump	rate (gpm):	2,000	Min. Gauge Readi	ing (cfs):	175.00	Min. Passby (cf	s) 106.30
	DEP Commer	nts:					
Source	Middle Island (Creek @ Mees	Withdrawal Site		Pleasants	Owner:	Sarah E. Mees
Start Date	End Date	T	otal Volume (gal)	Max. daily p	urchase (gal)	Intake Latitude:	Intake Longitude:
6/23/2014	6/23/2015		8,410,000			39.43113	-81.079567
☐ Regulated	Stream?		Ref. Gauge ID): 311450	0	MIDDLE ISLAND CREEK AT	LITTLE, WV
Max. Pump	rate (gpm):	3,360	Min. Gauge Read	ing (cfs):	52.59	Min. Passby (cf	s) 47.63
	DEP Commer	nts:					
Source	Middle Island (Creek @ Daws	on Withdrawal		Tyler	Owner: G a	ary D. and Rella A. Dawson
Start Date	End Date	Т	otal Volume (gal)	Max. daily p	ırchase (gal)		Intake Longitude:
6/23/2014	6/23/2015		8,410,000			39.379292	-80.867803
☐ Regulated	Stream?		Ref. Gauge ID): 311450	0	MIDDLE ISLAND CREEK AT	LITTLE, WV
Max. Pump	rate (gpm):	3,000	Min. Gauge Read	ing (cfs):	76.03	Min. Passby (cf	(s) 28.83
	DEP Commer	nts:					

Source McElroy Creek @ Forest Withdrawal Tyler Owner: Forest C. & Brenda L. Moore Start Date **End Date** Max. daily purchase (gal) Total Volume (gal) Intake Latitude: Intake Longitude: 6/23/2014 6/23/2015 8,410,000 39.39675 -80.738197 ☐ Regulated Stream? Ref. Gauge ID: 3114500 MIDDLE ISLAND CREEK AT LITTLE, WV Max. Pump rate (gpm): 1,000 Min. Gauge Reading (cfs): 74.77 Min. Passby (cfs) 13.10 **DEP Comments:** Source Meathouse Fork @ Gagnon Withdrawal Doddridge Owner: George L. Gagnon and Susan C. Gagnon Start Date **End Date** Max. daily purchase (gal) Total Volume (gal) Intake Latitude: Intake Longitude: 6/23/2014 6/23/2015 8,410,000 39.26054 -80.720998 Regulated Stream? Ref. Gauge ID: 3114500 MIDDLE ISLAND CREEK AT LITTLE, WV 1,000 Min. Gauge Reading (cfs): Max. Pump rate (gpm): 71.96 Min. Passby (cfs) 11.74 **DEP Comments:** Source Meathouse Fork @ Whitehair Withdrawal Doddridge Owner: **Elton Whitehair End Date** Max. daily purchase (gal) Intake Latitude: Intake Longitude: Start Date Total Volume (gal) 6/23/2015 39.211317 -80.679592 6/23/2014 8,410,000 Regulated Stream? Ref. Gauge ID: MIDDLE ISLAND CREEK AT LITTLE, WV 3114500 7.28 Max. Pump rate (gpm): 1,000 Min. Gauge Reading (cfs): 69.73 Min. Passby (cfs) **DEP Comments:**

Source Tom's Fork @ Erwin Withdrawal Doddridge Owner: John F. Erwin and Sandra E. Erwin Start Date **End Date** Total Volume (gal) Max. daily purchase (gal) Intake Latitude: Intake Longitude: 6/23/2014 6/23/2015 8,410,000 39.174306 -80.702992 ☐ Regulated Stream? Ref. Gauge ID: 3114500 MIDDLE ISLAND CREEK AT LITTLE, WV Max. Pump rate (gpm): 1,000 Min. Gauge Reading (cfs): 69.73 0.59 Min. Passby (cfs) **DEP Comments:** Source Arnold Creek @ Davis Withdrawal Doddridge Owner: **Jonathon Davis** Start Date **End Date** Total Volume (gal) Max. daily purchase (gal) Intake Latitude: Intake Longitude: 8,410,000 6/23/2014 6/23/2015 39.302006 -80.824561 Regulated Stream? Ref. Gauge ID: 3114500 MIDDLE ISLAND CREEK AT LITTLE, WV Max. Pump rate (gpm): 1,000 Min. Gauge Reading (cfs): Min. Passby (cfs) 3.08 69.73 **DEP Comments:** Source **Buckeye Creek @ Powell Withdrawal** Doddridge Owner: **Dennis Powell** Start Date **End Date** Total Volume (gal) Max. daily purchase (gal) Intake Latitude: Intake Longitude: 6/23/2014 6/23/2015 8,410,000 39.277142 -80.690386 ☐ Regulated Stream? Ref. Gauge ID: 3114500 MIDDLE ISLAND CREEK AT LITTLE, WV Max. Pump rate (gpm): 1,000 Min. Gauge Reading (cfs): 69.73 Min. Passby (cfs) 4.59

DEP Comments:

Source South Fork of Hughes River @ Knight Withdrawal Ritchie Owner: Tracy C. Knight & Stephanie C. Knight Start Date **End Date** Total Volume (gal) Max. daily purchase (gal) Intake Latitude: Intake Longitude: 6/23/2014 6/23/2015 8,410,000 39.198369 -80.870969 Regulated Stream? **JOUTH FORK HUGHES RIVER BELOW MACFARLAN, WI** Ref. Gauge ID: 3155220 Max. Pump rate (gpm): 3,000 Min. Gauge Reading (cfs): 39.80 Min. Passby (cfs) 1.95 **DEP Comments:** North Fork of Hughes River @ Davis Withdrawal Ritchie Source Owner: Lewis P. Davis and Norma J. Davis Start Date **End Date** Total Volume (gal) Max. daily purchase (gal) Intake Latitude: Intake Longitude: 6/23/2014 6/23/2015 8,410,000 39.322363 -80.936771 Regulated Stream? **JOUTH FORK HUGHES RIVER BELOW MACFARLAN, W**\ Ref. Gauge ID: 3155220 Max. Pump rate (gpm): 1,000 Min. Gauge Reading (cfs): 35.23 Min. Passby (cfs) 2.19

DEP Comments:

Source Summary

WMP-01572

API Number:

047-017-06398

Operator:

Antero Resources

McMillan Unit 2H

Purchased Water

 Source Ohio River @ Select Energy Pleasants

Owner:

Select Energy

Start Date

End Date

Total Volume (gal)

Max, daily purchase (gal)

Intake Latitude:

Intake Longitude:

6/23/2014

6/23/2015

8,410,000

500,000

39.346473

-81.338727

✓ Regulated Stream?

Ohio River Min. Flow

Ref. Gauge ID:

9999998

Ohio River Station: Racine Dam

Max. Pump rate (gpm):

1,680

Min. Gauge Reading (cfs):

7,216.00

Min. Passby (cfs)

DEP Comments:

Refer to the specified station on the National Weather Service's Ohio River forecast website: http://www.erh.noaa.gov/ohrfc//flows.shtml

Source

Middle Island Creek @ Solo Construction

Ohio River Min. Flow

Pleasants

Owner:

Solo Construction, LLC

Start Date

End Date

Total Volume (gal)

Max. daily purchase (gal)

Intake Latitude: Intake Longitude:

6/23/2014

6/23/2015

8,410,000

1,000,000

9999999

39.399094

-81.185548

✓ Regulated Stream?

Max. Pump rate (gpm):

Min. Gauge Reading (cfs):

Ref. Gauge ID:

6,468.00

Min. Passby (cfs)

Ohio River Station: Willow Island Lock & Dam

DEP Comments:

Elevation analysis indicates that this location has the same elevation as Middle Island Creek's pour point into the Ohio River. As such, it is deemed that water flow at this location is heavily influenced by the Ohio River.

Source

Claywood Park PSD

Wood

Owners

Claywood Park PSD

Start Date

End Date

Total Volume (gal)

Max. daily purchase (gal)

Intake Latitude: Intake Longitude:

6/23/2014

6/23/2015

8,410,000

✓ Regulated Stream?

Ref. Gauge ID:

9999998

Ohio River Station: Racine Dam

Max. Pump rate (gpm):

Min. Gauge Reading (cfs):


7,216.00

Min. Passby (cfs)


DEP Comments:

Elevation analysis indicates that this location has approximately the same elevation as Little Kanawha's pour point into the Ohio River. As such, it is deemed that water flow at this location is heavily influenced by the Ohio River.

o Jource	Juli valley Fublic Self	nce District	Панть	on Owner.	oun valley Po
Start Date	End Date	Total Volume (gal)	Max. daily purchase	(gal) Intake	Latitude: Intake Longitud
6/23/2014	6/23/2015	8,410,000	200,000		-
☑ Regulated	Stream? Stonewall Ja	ackson Dam Ref. Gauge I	D: 3061000	WEST FORK RIVI	ER AT ENTERPRISE, WV
Max. Pump	rate (gpm):	Min. Gauge Read	ding (cfs): 171.	48 Min.	Passby (cfs)
	DEP Comments:				




Water Availability Profile




Water Availability Assessment of Location

Upstream Demand (cfs): Downstream Demand (cfs):	0.00
SACRAM A CERTAIN MARKET A SARAH CARAMININA A MARKATAN AND A CARAMININA	0.00
Pump rate (cfs):	3.74
Headwater Safety (cfs):	0.00
Ungauged Stream Safety (cfs):	0.00

[&]quot;Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.







Water Availability Assessment of Location

Base Threshold (cfs):

Upstream Demand (cfs):

Downstream Demand (cfs):

Pump rate (cfs):


Headwater Safety (cfs):

Ungauged Stream Safety (cfs):


O.00

Min. Gauge Reading (cfs):

Passby at Location (cfs):




Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	50,956.00		
2	54,858.00		*
3	73,256.00	*	*
3	62,552.00	9	-
5	43,151.00	3	¥
6	27,095.00	9	
7	17,840.00		
8	14,941.00	*	5.
9	14,272.00	*	
10	17,283.00		
11	29,325.00	32	*
12	46,050.00	6	




Water Availability Assessment of Location

Upstream Demand (cfs):	0.00
Downstream Demand (cfs):	0.00
Pump rate (cfs):	
Headwater Safety (cfs):	0.00
Ungauged Stream Safety (cfs):	0.00
Min. Gauge Reading (cfs):	
Passby at Location (cfs):	



Water Availability Profile



Water Availability Assessment of Location

Base Threshold (cfs):

Upstream Demand (cfs):

Downstream Demand (cfs):

Pump rate (cfs):

Headwater Safety (cfs):

Ungauged Stream Safety (cfs):

O.00


Min. Gauge Reading (cfs):

Passby at Location (cfs):

[&]quot;Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.



Water Availability Profile



Water Availability Assessment of Location

Upstream Demand (cfs):	0.00
Downstream Demand (cfs):	0.00
Pump rate (cfs):	7.49
Headwater Safety (cfs):	0.00
Ungauged Stream Safety (cfs):	0.00

"Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.


26,300.00

41,300.00

11 12



Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	1,630.82	6	-
2	1,836.14		ä
3	2,365.03		
4	1,352.59		
5	1,388.37	#	
6 7	695.67	*	+:
7	450.73	*	2
8	430.37	~	3
9	299.45	= = = = = = = = = = = = = = = = = = = =	5
10	293.59		*
11	736.74	*	*
12	1,257.84		




Min. Gauge Reading (cfs): Passby at Location (cfs):	
Ungauged Stream Safety (cfs):	0.00
Headwater Safety (cfs):	0.00
Pump rate (cfs):	4.46
Downstream Demand (cfs):	0.00
Upstream Demand (cfs):	24.29
Base Threshold (cfs):	

[&]quot;Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

WMP-01572 API/ID Number: 047-017-06398 Operator: Antero Resources McMillan Unit 2H 29601 Source Name West Fork River @ McDonald Withdrawal Source Latitude: 39.16761 Source ID: **David Shrieves** Source Longitude: -80.45069 HUC-8 Code: 5020002 Anticipated withdrawal start date: 6/23/2014 Drainage Area (sq. mi.): 314.91 Harrison County: 6/23/2015 Anticipated withdrawal end date: **Endangered Species?** ✓ Mussel Stream? Total Volume from Source (gal): 8,410,000 Trout Stream? ☐ Tier 3? Max. Pump rate (gpm): 3,000 Regulated Stream? Stonewall Jackson Dam Proximate PSD? Max. Simultaneous Trucks: 0 Max. Truck pump rate (gpm) Gauged Stream? 3061000 WEST FORK RIVER AT ENTERPRISE, WV Reference Gaug 759.00 234 Drainage Area (sq. mi.) Gauge Threshold (cfs):

Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	964.98	*	181
2	1,086.47	8	(40)
3	1,399.42	*	⊕ ⊕
4	800.34	÷	140
5	821.52		· F
6	411.64	2	12
7	266.70	8	
8	254.66	*	(±)
9	177.19	*	€
10	173.72	*	360
11	435.94	2	
12	744.28	2	12

Water Availability Profile




Water Availability Assessment of Location

Base Threshold (cfs):	-
Upstream Demand (cfs):	24.29
Downstream Demand (cfs):	0.00
Pump rate (cfs):	6.68
Headwater Safety (cfs):	24.27
Ungauged Stream Safety (cfs):	0.00
Min. Gauge Reading (cfs):	-
Passby at Location (cfs):	

WMP-01572 API/ID Number: 047-017-06398 Operator: Antero Resources McMillan Unit 2H Source Latitude: 39.16422 Source ID: 29602 Source Name West Fork River @ GAL Withdrawal **David Shrieves** Source Longitude: -80.45173 5020002 HUC-8 Code: Anticipated withdrawal start date: 6/23/2014 313.67 Harrison Drainage Area (sq. mi.): County: Anticipated withdrawal end date: 6/23/2015 **Endangered Species?** ✓ Mussel Stream? 8,410,000 Total Volume from Source (gal): Trout Stream? ☐ Tier 3? 2,000 Max. Pump rate (gpm): Stonewall Jackson Dam Regulated Stream? Proximate PSD? Max. Simultaneous Trucks: 0 Gauged Stream? Max. Truck pump rate (gpm) 0 3061000 Reference Gaug WEST FORK RIVER AT ENTERPRISE, WV 759.00 Drainage Area (sq. mi.) Gauge Threshold (cfs): 234

Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	961.18	£ .	12:
2	1,082.19		p.
3	1,393.91	5	. 60
4	797.19	T 5:	
5	818.28	*	(e)
6	410.02	*	(#1
7	265,65	#	k:
8	253.65		10 10
9	176.49	÷	5
10	173.04		5
11	434.22		5
12	741.35	*	*:

Water Availability Profile





Water Availability Assessment of Location

Base Threshold (cfs):	57
Upstream Demand (cfs):	24.29
Downstream Demand (cfs):	0.00
Pump rate (cfs):	4.46
Headwater Safety (cfs):	24.18
Ungauged Stream Safety (cfs):	0.00
Min. Gauge Reading (cfs):	
Passby at Location (cfs):	9

WMF	-01572	API/ID N	umber: 047-017- McMillan Unit 2H	06398 Oper	rator: Antero F	Resources
Source ID: 29603 S	Source Name	Middle Island Cre	ek @ Mees Withdraw	al Site	oodiica marrada.	43113 .079567
HUC-8 Code: Drainage Are Endangered Speci Trout Stream? Regulated Stream Proximate PSD? Gauged Stream?	ea (sq. mi.): es? 🗹 Mu	201 484.78 Coun issel Stream? r 3?	ty: Pleasants	Anticipated v	vithdrawal start date: withdrawal end date: me from Source (gal): ax. Pump rate (gpm); Max. Simultaneou Max. Truck pump ra	6/23/2014 6/23/2015 8,410,000 3,360
Reference Gau		458.00 MIDDLE I	SLAND CREEK AT LITTL		Gauge Threshold (cfs):	45

Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	519.88	55.12	465.14
2	653.95	55.12	599.22
3	731.75	55.12	677.01
4	543.38	55.12	488.65
5	286.64	55.12	231.90
6	100.10	55.12	45.36
7	56.65	55.12	1.91
8	46.64	55.12	-8.10
9	23.89	55.12	-30.85
10	30.01	55.12	-24.72
11	146.56	55.12	91.83
12	358.10	55.12	303.37





Water Availability Assessment of Location

Min. Gauge Reading (cfs): Passby at Location (cfs):	52.49 47.63
Ungauged Stream Safety (cfs):	0.00
Headwater Safety (cfs):	0.00
Pump rate (cfs):	7.49
Downstream Demand (cfs):	0.00
Upstream Demand (cfs):	0.00
Base Threshold (cfs):	47.63

WMP-01572

API/ID Number:

047-017-06398

Operator:

Antero Resources

McMillan Unit 2H

Source ID: 29604

Source Name

Middle Island Creek @ Dawson Withdrawal

Source Latitude: 39.379292

Source Longitude: -80.867803

HUC-8 Code:

5030201

181.34

Anticipated withdrawal start date:

6/23/2014

Drainage Area (sq. mi.):

Tyler

Anticipated withdrawal end date:

6/23/2015

Endangered Species?

✓ Mussel Stream?

Total Volume from Source (gal):

8,410,000

Trout Stream?

Tier 3?

Max. Pump rate (gpm):

3,000

Regulated Stream? Proximate PSD?

Gary D. and Rella A. Dawson

County:

Max. Simultaneous Trucks:

Gauged Stream?

3114500

MIDDLE ISLAND CREEK AT LITTLE, WV

Max. Truck pump rate (gpm)

Drainage Area (sq. mi.)

Reference Gaug

458.00

Gauge Threshold (cfs):

45

Month	Median monthly flow (cfs)	Threshold (+ pump	<u>Available</u> water (cfs)
1	194.47	42.06	152.68
2	244.62	42.06	202.83
3	273.72	42.06	231.93
4	203.26	42.06	161.47
5	107.22	42.06	65.43
6	37,44	42.06	-4,35
7	21.19	42.06	-20.60
8	17.45	42.06	-24.34
9	8.94	42.06	-32.85
10	11.23	42.06	-30.56
11	54.82	42.06	13.04
12	133.96	42.06	92.17

Water Availability Profile 300 200 100 1 9 11 7 10 12 Median Monthly Flow - Threshold

Water	Availability	Assessment	of	Location

Base Threshold (cfs):

Upstream Demand (cfs):

17.82

Downstream Demand (cfs):

13.10 6.55

Pump rate (cfs):

6.68

Headwater Safety (cfs):

4.45

0.00

Min. Gauge Reading (cfs):

Ungauged Stream Safety (cfs):

76.03

Passby at Location (cfs):


28.82

[&]quot;Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

WMP-01572	API/ID Number:	047-017-06398	Operator:	Antero Re	esources
	McMill	an Unit 2H			
Source ID: 29605 Source Name	McElroy Creek @ Forest Wi	thdrawal	Source L	atitude: 39.3	9675
	Forest C. & Brenda L. Moore	е	Source Lo	ngitude: -80.	738197
Drainage Area (sq. mi.): Endangered Species?	88.85 County: ussel Stream? er 3?	Tyler	Anticipated withdrawal s Anticipated withdrawal Total Volume from So Max. Pump ra	end date: urce (gal):	6/23/2014 6/23/2015 8,410,000 1,000
☐ Gauged Stream?			Ma	x. Truck pump rat	e (gpm) 0
Reference Gaug 3114	500 MIDDLE ISLAND CRI	EEK AT LITTLE, WV			
Drainage Area (sq. mi.)	458.00		Gauge Thre	eshold (cfs):	45

<u>Month</u>	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	95.28	19.78	75.68
2	119.86	19.78	100.25
3	134.11	19.78	114.51
4	99.59	19.78	79.99
5	52.54	19.78	32.93
6	18.35	19.78	-1.26
7	10.38	19.78	-9.22
8	8.55	19.78	-11.05
9	4.38	19.78	-15.23
10	5.50	19.78	-14.10
11	26.86	19.78	7.26
12	65.63	19.78	46.03

Water Availability Profile




W	ater	Ava	ilabi	lity	Asses	smer	nt o	Loca	tion

Base Threshold (cfs):	8.73
Upstream Demand (cfs):	4.46
Downstream Demand (cfs):	0.00
Pump rate (cfs):	2.23
Headwater Safety (cfs):	2.18
Ungauged Stream Safety (cfs):	2.18
Min. Gauge Reading (cfs):	74.19
Passby at Location (cfs):	13.09

WMP-01572	API/ID Numb	er: 047-017-0639 cMillan Unit 2H	98 Operator: Anter	o Resources
Source ID: 29606 Source Name	Meathouse Fork @ Ga	A CONTRACTOR AND CONT	Source Latitude:	39.26054
	George L. Gagnon and	Susan C. Gagnon	Source Longitude:	-80.720998
	60.6 County: ussel Stream? er 3?	Doddridge	Anticipated withdrawal start date: Anticipated withdrawal end date: Total Volume from Source (gal): Max. Pump rate (gpm): Max. Simultan Max. Truck pum	6/23/2015 8,410,000 1,000 leous Trucks: 0
Reference Gaug 31145	MIDDLE ISLAN	D CREEK AT LITTLE, W	/V	
Drainage Area (sq. mi.)	458.00		Gauge Threshold (cfs): 45

Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	64.99	13.39	51.70
2	81.75	13.39	68.46
3	91.47	13.39	78,19
4	67.93	13.39	54.64
5	35.83	13.39	22.55
6	12.51	13.39	-0.77
7	7.08	13.39	-6.20
8	5.83	13.39	-7.45
9	2.99	13.39	-10.30
10	3.75	13.39	-9.53
11	18.32	13.39	5.04
12	44.76	13.39	31.48

Water Availability Profile




Water Availability Assessment of Location

Min. Gauge Reading (cfs): Passby at Location (cfs):	71.96 11.74
Ungauged Stream Safety (cfs):	1.49
Headwater Safety (cfs):	1.49
Pump rate (cfs):	2.23
Downstream Demand (cfs):	2.81
Upstream Demand (cfs):	2.23
Base Threshold (cfs):	5.95

WMP-01572 API/ID Num	ber: 047-017-06398 McMillan Unit 2H	Operator: Antero I	Resources
ource ID: 29607 Source Name Meathouse Fork @ V	Whitehair Withdrawal	775	211317 0.679592
HUC-8 Code: 5030201 Drainage Area (sq. mi.): 30.37 County: ✓ Endangered Species? ✓ Mussel Stream? ☐ Trout Stream? ☐ Tier 3? ☐ Regulated Stream? ☐ Proximate PSD? ☐ Gauged Stream?	Doddridge	Anticipated withdrawal start date: Anticipated withdrawal end date: Total Volume from Source (gal): Max. Pump rate (gpm): Max. Simultaneon	
Reference Gaug 3114500 MIDDLE ISLA Drainage Area (sq. mi.) 458.00	ND CREEK AT LITTLE, WV	Gauge Threshold (cfs):	45

Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	32.57	6.70	26.15
2	40.97	6.70	34.55
3	45.84	6.70	39.42
4	34.04	6.70	27.62
5	17.96	6.70	11.54
6	6.27	6.70	-0.15
7	3.55	6.70	-2.87
8	2.92	6.70	-3.50
9	1.50	6.70	-4.92
10	1.88	6.70	-4.54
11	9.18	6.70	2.76
12	22.43	6.70	16.01

Water Availability Profile




Water Availability Assessment of Location

Passby at Location (cfs):	7.29
Min. Gauge Reading (cfs):	69.73
Ungauged Stream Safety (cfs):	0.75
Headwater Safety (cfs):	0.75
Pump rate (cfs):	2.23
Downstream Demand (cfs):	2.81
Upstream Demand (cfs):	0.00
Base Threshold (cfs):	2.98

WMP-01572	API/ID Number: 047-017-0 McMillan Unit 2H	6398 Operator; Antero F	lesources
Source ID: 29608 Source Name	Tom's Fork @ Erwin Withdrawal John F. Erwin and Sandra E. Erwin		174306 .702992
HUC-8 Code: 50300 Drainage Area (sq. mi.): □ Endangered Species? ✓ Mu □ Trout Stream? □ Tien □ Regulated Stream? □ Proximate PSD?	4.01 County: Doddridge ssel Stream?	Anticipated withdrawal start date: Anticipated withdrawal end date: Total Volume from Source (gal): Max. Pump rate (gpm): Max. Simultaneou	6/23/2014 6/23/2015 8,410,000 1,000 s Trucks: 0
☐ Gauged Stream?		Max. Truck pump re	te (gpm) 0
Reference Gaug 31145 Drainage Area (sq. mi.)	00 MIDDLE ISLAND CREEK AT LITTLE 458.00	Gauge Threshold (cfs):	45

Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	4.30	2.82	1.88
2	5.41	2.82	2.98
3	6.05	2.82	3.63
4	4.49	2.82	2.07
5	2.37	2.82	-0.05
6	0.83	2.82	-1.60
7	0.47	2.82	-1.96
8	0.39	2.82	-2.04
9	0.20	2.82	-2.23
10	0.25	2.82	-2.18
11	1.21	2.82	-1.21
12	2.96	2.82	0.54

Water Availability Profile



Water Availability Assessment of Location

Min. Gauge Reading (cfs):	69.73
Ungauged Stream Safety (cfs):	0.10
Headwater Safety (cfs):	0.10
Pump rate (cfs):	2.23
Downstream Demand (cfs):	0.00
Upstream Demand (cfs):	0.00
Base Threshold (cfs):	0.39

Passby at Location (cfs):


"Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

0.59

WMP-01572	API/ID Number:	047-017-06398	Operator: Antero	Resources
	McMill	an Unit 2H		
Source ID: 29609 Source Name	Arnold Creek @ Davis Witho	drawal	Source Latitude: 39	9.302006
	Jonathon Davis		Source Longitude: -8	30.824561
		oddridge Ant	cipated withdrawal start date: cicipated withdrawal end date: otal Volume from Source (gal): Max. Pump rate (gpm):	6/23/2014 6/23/2015 8,410,000 1,000
Proximate PSD?			Max. Simultane	ous Trucks: 0
☐ Gauged Stream?			Max. Truck pump	rate (gpm) 0
Reference Gaug 31145	00 MIDDLE ISLAND CRI	EEK AT LITTLE, WV		
Drainage Area (sq. mi.)	458.00		Gauge Threshold (cfs):	45

Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	22.34	5.30	17.29
2	28.10	5.30	23.05
3	31.44	5.30	26.39
- 4	23.35	5.30	18.30
.5	12.32	5.30	7.26
5	4.30	5.30	-0.75
7	2.43	5.30	-2.62
8	2.00	5.30	-3.05
9	1.03	5.30	-4.03
10	1.29	5.30	-3.76
11	6.30	5.30	1.25
12	15.39	5.30	10.34

Water Availability Profile



Water Availability Assessment of Location

Base Threshold (cfs):	2.05
Upstream Demand (cfs):	0.00
Downstream Demand (cfs):	0.00
Pump rate (cfs):	2.23
Headwater Safety (cfs):	0.51
Ungauged Stream Safety (cfs):	0.51
Min. Gauge Reading (cfs):	69.73
Passby at Location (cfs):	3.07


Passby at Location (cfs): 3.

[&]quot;Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

WMP-01572	API/ID Number: McMillar	047-017-06398 n Unit 2H	Operator: Ante	ro Resources
Source ID: 29610 Source Name	Buckeye Creek @ Powell Wit Dennis Powell	hdrawal		39.277142 -80.690386
		ddridge Antic	pated withdrawal start date ipated withdrawal end date al Volume from Source (gal) Max. Pump rate (gpm):	6/23/2015 8,410,000
☐ Proximate PSD? ☐ Gauged Stream?			Max. Simultar Max. Truck pun	
Reference Gaug 3114! Drainage Area (sq. mi.)	MIDDLE ISLAND CREE	EK AT LITTLE, WV	Gauge Threshold (cfs	i): 45

<u>Month</u>	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	33.41	6.82	26.95
2	42.02	6.82	35.56
3	47.02	6.82	40.56
4	34.92	6.82	28.46
5	18.42	6.82	11.96
6	6.43	6.82	-0.03
7	3.64	6.82	-2.82
8	3.00	6.82	-3.46
9	1.53	6.82	-4.92
10	1.93	6.82	-4.53
11	9.42	6.82	2.96
12	23.01	6.82	16.55

Water Availability Profile



Water Availability Assessment of Location


Min. Gauge Reading (cfs): Passby at Location (cfs):	69.73 4.59
Ungauged Stream Safety (cfs):	0.77
Headwater Safety (cfs):	0.77
Pump rate (cfs):	2.23
Downstream Demand (cfs):	0.00
Upstream Demand (cfs):	0.00
Base Threshold (cfs):	3.06

Source Detail

	WMP-01572	API/ID Numb	oer: 047-017-06398	Operator: Antero F	Resources
		N	AcMillan Unit 2H		
ource ID:	29611 Source Name	South Fork of Hughes	River @ Knight Withdrawa	Source Latitude: 39.	198369
		Tracy C. Knight & Step	hanie C. Knight	Source Longitude: -80	.870969
Endang Trout S	rainage Area (sq. mi.): gered Species?	16.26 County: lussel Stream? er 3?	Ritchie A	ticipated withdrawal start date: nticipated withdrawal end date: Total Volume from Source (gal): Max. Pump rate (gpm):	6/23/2014 6/23/2015 8,410,000 3,000
	ate PSD? d Stream?			Max. Simultaneou Max. Truck pump ra	
Refe	erence Gaug 3155	SOUTH FORK	HUGHES RIVER BELOW MA	ACFARLAN, WV	
Drai	inage Area (sq. mi.)	229.00		Gauge Threshold (cfs):	22

Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	45.67	14.26	31.44
2	59.55	14.26	45.31
3 4	65.21	14.26	50.97
4	36.87	14.26	22.63
5	25.86	14.26	11.63
6	13.90	14.26	-0.33
7	6.89	14.26	-7.34
8	3.98	14.26	-10.25
9	4.79	14.26	-9.45
10	5.20	14.26	-9.04
11	15.54	14.26	1.30
12	32.06	14.26	17.82

Water Availability Profile



Water Availability Assessment of Location

Min. Gauge Reading (cfs): Passby at Location (cfs):	39.80 1.95
Ungauged Stream Safety (cfs):	0.00
Headwater Safety (cfs):	0.39
Pump rate (cfs):	6.68
Downstream Demand (cfs):	0.00
Upstream Demand (cfs):	5.62
Base Threshold (cfs):	1.56


"Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

Source Detail

WMP- 01572	API/ID N	lumber: 047-017-0	06398 Operator: Antero	Resources
		McMillan Unit 2H		
Source ID: 29612 Source N	ame North Fork of Hu Lewis P. Davis an	ghes River @ Davis Witl d Norma J. Davis	The second secon	.322363 0.936771
HUC-8 Code: Drainage Area (sq. m ✓ Endangered Species? ☐ Trout Stream? ☐ Regulated Stream? ☐ Proximate PSD? ☐ Gauged Stream?	5030203 i.): 15.18 Coun Mussel Stream? Tier 3?	ty: Ritchie	Anticipated withdrawal start date: Anticipated withdrawal end date: Total Volume from Source (gal): Max. Pump rate (gpm): Max. Simultaneo Max. Truck pump r	
Reference Gaug Drainage Area (sq. mi.)		ORK HUGHES RIVER BEL	OW MACFARLAN, WV Gauge Threshold (cfs):	22

Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	42.64	4.42	38.36
2	55.59	4.42	51.32
3	60.88	4.42	56.60
4	34.42	4.42	30.14
5	24.15	4.42	19.87
6	12.98	4.42	8.70
7	6.44	4.42	2.16
8	3.72	4.42	-0.56
9	4.47	4.42	0.19
10	4.85	4.42	0.57
11	14.50	4.42	10.23
12	29.93	4.42	25.65

Water Availability Profile



Water Availability Assessment of Location

Base Threshold (cfs):	1.46		
Upstream Demand (cfs):	0.00		
Downstream Demand (cfs):	0.00		
Pump rate (cfs):	2.23		
Headwater Safety (cfs):	0.36		
Ungauged Stream Safety (cfs):	0.36		
Min. Gauge Reading (cfs):	35.23		
Passby at Location (cfs):	2.19		

"Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

west virginia department of environmental protection



Water Management Plan: Secondary Water Sources



WMP-01572

API/ID Number

047-017-06398

Operator:

Antero Resources

McMillan Unit 2H

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

Lake/Reservior

Source ID: 29617 Source Name

City of Salem Reservior (Lower Dog Run)

Source start date:

6/23/2014

Public Water Provider

Source end date:

6/23/2015

Source Lat:

39.28834

Source Long:

-80.54966

County

Harrison

Max. Daily Purchase (gal)

1,000,000

Total Volume from Source (gal):

8,410,000

047-017-06398

Operator:

Antero Resources

McMillan Unit 2H

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

Source ID: 29618 Source Name

Pennsboro Lake

Source start date:

6/23/2014

Source end date:

6/23/2015

Source Lat:

39.281689

Source Long:

-80.925526

County

Ritchie

Max. Daily Purchase (gal)

Total Volume from Source (gal):

8,410,000

DEP Comments:

Source ID: 29619 Source Name

Powers Lake (Wilderness Water Park Dam)

Source start date:

6/23/2014

Private Owner

Source end date:

6/23/2015

Source Lat:

39.255752

Source Long:

-80.463262

County

Harrison

Max. Daily Purchase (gal)

Total Volume from Source (gal):

8,410,000

WMP-01572 API/ID Number 047-017-06398 Operator: Antero Resources

McMillan Unit 2H

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- •For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- •For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

Source ID: 29620 Source Name Powers Lake Two Source start date: 6/23/2014 6/23/2015 Source end date: 39.247604 Source Lat: Source Long: -80.466642 Harrison County Max. Daily Purchase (gal) 8,410,000 Total Volume from Source (gal): **DEP Comments:**

McMillan Unit 2H

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

Other

Source ID: 29621 Source Name

Source Lat:

Poth Lake (Landowner Pond)

Source start date: Source end date: 6/23/2014 6/23/2015

Private Owner

39.221306

-80.463028

County

Harrison

Max. Daily Purchase (gal)

Total Volume from Source (gal):

8,410,000

DEP Comments:

Source ID: 29622 Source Name

Williamson Pond (Landowner Pond)

Source start date:

6/23/2014

Source end date:

6/23/2015

Source Lat:

39.19924

Source Long:

Source Long:

-80.886161

County

Ritchie

Max. Daily Purchase (gal)

Total Volume from Source (gal):

8,410,000

WMP-01572	API/ID Number	047-017-06398	Operator:	Antero Resources
		FALSE CONTRACTOR AND ADMINISTRAÇÃO (ACADEMA CADA CADA CADA CADA CADA CADA CADA CA		

McMillan Unit 2H

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- •For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- •For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

Source ID: 29623 Eddy Pond (Landowner Pond) Source Name Source start date: 6/23/2014 Source end date: 6/23/2015 39.19924 Source Long: -80.886161 Ritchie Source Lat: County 8,410,000 Max. Daily Purchase (gal) Total Volume from Source (gal): DEP Comments:

Source ID: 29624 Source Name Hog Lick Quarry Source start date: 6/23/2014
Industrial Facility Source end date: 6/23/2015

Source Lat: 39.419272 Source Long: -80.217941 County Marion

Max. Daily Purchase (gal) 1,000,000 Total Volume from Source (gal): 8,410,000

WMP-01572

API/ID Number

047-017-06398

Operator:

Antero Resources

McMillan Unit 2H

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- •For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- •For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.


Source ID: 29625 Source Name Glade Fork Mine Source start date: 6/23/2014 Industrial Facility Source end date: 6/23/2015 38.965767 -80.299313 Source Lat: Upshur Source Long: County 1,000,000 8,410,000 Max. Daily Purchase (gal) Total Volume from Source (gal): **DEP Comments:**

Recycled Frac Water


Source ID: 29626 Source Name Various Source start date: 6/23/2014
Source end date: 6/23/2015
Source Lat: Source Long: County

Max. Daily Purchase (gal) Total Volume from Source (gal): 8,410,000

DEP Comments: Sources may include, but are not limited to: Hoskinson Unit 2H



Antero Resources Corp APPALACHIAN BASIN McMillan Unit 2H Doddridge County REMARKS QUADRANGLE: SMITHBURG WATERSHED: LITTLE FLINT RUN DISTRICT: GRANT By: ECM 1 2,500 FEET



54 y 6/19/2013



+80-43-16,4840

66-43-15.3000

-80-43-18.2484

-60-43-15-9988

\$8-21-47,7869

38-21-47 8249

39-21-47.0024

39-21-47,8881







THIS DOCUMENT PREPARED FOR ANTERO RESOURCES APPALACHIAN CORP

WELL LOCATION RESTRICTIONS

THE PAD COMPLIES WITH THE FOLLOWING RESTRICTIONS

216701.3257

216798,0011

SUSHICA UNIT 2H

HOSKINSON UNIT 2H

-250 FROM AN EXISTING WELL OR DEVELOPED SPRING USED FOR HUMAN OR DOMESTIC ANNALS 162Y FROM AN OCCUPIED OWILLING OR BARD MEASURED PROM THE CENTER OF THE PAO

1997 FROM EDGE OF DISTURDANCE TO WETLA

1023032.5004

1023242.2579

DRILL PAD ELEVATION-1915/F

SUFFROM EDGE OF DISTURBANCE TO NATUR -1000 OF SURFACE OR GROUND WATER BITAK

N GREATER THAN 2900SF USED FOR POULTRY NOON, PERENNAL, STREAMS, NATURAL OR AR NALLY REPRODUCING TROUT STREAMS NE TO A PUBLIC WATER SUPPLY		N, QUANTITI ON SEQUEN DRILL
DPLAIN CONDITIONS		
N ACTIVITIES TAKE PLACE IN PLOCOPLAIR.	960	E 2 Z Z
COUNTY FLOODFLAIN COORDINATOR:	100	ETSTE
LETED	HW.	IS S S
er DRAWENCE	4446	日の日

COVER PASE & LOCATION MAP	- 1
SCHEDULE OF CHANTITIES	1.2
CONSTRUCTION, GENERAL AND ESS NOTES	- 76
EXISTING CONDITIONS PLAN	. 4
OVERALL SITE PLAN	5
EROSION & SEDIMENT CONTROL PLAN	9.0
FINAL SITE DESIGN	10-13
DRILL PAD PROFILE & CROSS-SECTIONS	14
ROAD PROFILES	15-10
PAD NOAD CROSS-SECTIONS	17-00
CONSTRUCTION DETAILS	31-82
RECLAMATION PLAN	33.84

\$4011001300

ATTACHED MERG TO HAVE BEEN PREPARED IN ACCORDANCE WITH THE WEST VIRGINIA CODE OF STATE BULES, DIVISION OF ENVIRONMENTAL PROTECTION OFFICE OF OIL AND GAS \$25-4-21.

PRIGR TO THE COMMENCEMENT OF CONSTRUCTION ACTIVITIES.

ANTERO RESOURCES APPALACHIAN CORPORATION

Electronic Version of Plans Can Be Viewed at: Q\OIL GAS\SAY FILES\REVIEWS



PROJECT LOCATION

SITE LOCATIONS STATE PLANE NAD 83 (WV HORTH ZONE)

466		m. corres
		The state of the s
1.45	THE ACCOUNT OF THE PERSON NAMED IN	
The second secon	Marine Committee of the	
	The second secon	ORDODOUS AND A SET OF THE PROPERTY.
The second secon		
\$14 M		The state of the s
The state of the s	The state of	Marie
p)		
4		**
AND THE RESERVE OF THE PARTY OF	Commence of the commence of th	
	The same	Company of the compan
Except Of West	77	AND THE PARTY OF T
Chapely (III Wells	• CHESTNUT	
	• Orizontion	THE RESERVE OF THE PARTY OF THE
1 Contos	The state of the s	A CONTRACTOR OF THE PARTY OF TH
A STATE OF THE PARTY OF THE PAR	Contest there	A THE RESERVE AND A STREET
	THE RESERVE OF LOSS	
	THE RESERVE OF THE PARTY OF THE	
ar the second		
all the second	and the state of the second	Y THE THE PARTY OF
The second secon		
	1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	
E Comment	The state of the s	E. 1110 F. S.
The same of the sa	THE PERSON NAMED IN COLUMN	AND THE RESERVE OF THE PARTY OF
Mark Committee of the American	The second secon	
A WELL STREET		liva .
	The state of the s	Hara S
TO THE PARTY OF TH	The second district Address	Wat .
		The second secon
A STATE OF THE PARTY OF THE PAR	E	THE RESERVE TO SERVE
AT A STATE OF THE	8.6	Market Committee
	The state of the s	The second secon
THE RESERVE AND ADDRESS OF THE PARTY OF THE	The second secon	The state of the state of the state of

WATERSHED (HUCK): UTTLE MUSKINGUM-MIDDLE ISLAND

11.12

5.19

AFFECTED TAX PARCELS:

DRELL PAD

SPOIL PAD

TOTAL WOODED

MAIN ACCESS ROAD TO PAD AND TRUCK TURNOUTS

SMITHBURG 7.5 QUAD

DENZELE PRATT DENZELE PRATT DENZELE PRATT D8-202 PAGE 227 DB 202 PAGE 227 DB 195 PAGE 595 TM 5 PARCID, 20 TIM 5 PARCEL 10 TW 5 PARCEL 10

KOBERT J. SMITH DB 245 PAGE 824 TM 5 PARCEL 9

FEET

1,555.67

3,282,13

GROVE CHURCH TIM 5 PARCEL BD

DISTRICT	GRANT DISTN	GT -
8	TREAM IMPACTS	(LINEAR FEET)
DESCRIPT	NON	LINEAR FEET
RPW PERE	TRAN.	0.
NEW EN	EMERAL.	0.
PEN WETL	ANDS	0
RPW INTE	TRUTTING	
0.50	pero contra	- 3
WWW.AL		- 0

SKOVE CHURCH.

PROJECT LOCATION

SCALE 1" = 2000"

MOTE:	N.C	STR	EAN	(M	PACTS	WERE	ACCOU	ø
	FOR	t He	THE	BJ	BAILTH	PADS	HE DES	ø

	THEFT IN CO. EAST	26-51-41/8225	-00F43-10CE3	
	BEIGH ENTRANCE ROAD	39-21-44-2300	-90-44-04.80	
	CENTER OF PAD JUTM 60-17 M	14-4357120.002	£ 524019.000	
	TOTAL DISTURBAN	CE (ACRES)	1	
LAND OWNER		ARI	EA .	
DENZA F. PRATT [PAR. 10]		3,4	3.40	
DENZE F. PRATT (PAR. 196		0.0	-	

NOTE: A PORTION OF THE YOTAL LOD WAS ACCOUNTED. FOR IN THE RUSMITH PAD SITE DESIGN.

TOTAL DISTURBANCE (ACRE	58)
LAND OWNER	AREA
D0928. F. PRATT [PAR. 10]	3,40
DENZE, F. PRATT (PAR. 196	0.00
DENZIL F. PRATT [PAR. 20]	0.00
ROBERT A SMETH (PWR. 10)	0.00
TRESTEES CHESTNUT GROVE CHURCH (FAR. 30)	3.78

MISS UTILITY OF WEST VIRGINIA 1-800-245-4848 WEST VIRGINIA STATE LAW REQUIRES THAT YOU CALL TWO BUSINESS DAYS BEFORE YOU DIG IN THE STATE OF

PROJECT CONTACTS. ANTERO RESOURCES

204-899-3485-OFFICE

204-522-3542 EXT. S11

JICHN KAWCAK, ENGINEER

SURVEYOR & ENGINEER WHITE BROTHERS CONSULTING, LLC.

LEE SHYDER, P.S.

OPTICE 384-475-9778

405-277-6344

304-550-0484 TIMOTHY T. WHITE, P.E.

004-565-6477

304-673-6198 CELL


ANTHONY SWITH, FIELD ENGINEER

ELI WAGONER, ENVIRONMENTAL ENCINCER

AMRON KUNZLER, CONSTRUCTION SUPERVISOR.



TRUSTES CHESTNUT GROVE CHURCHOPAR. 30.15 31.82



FLOO DO SITE CONSTRUCTION PERMIT NEEDED FROM HECHAS STUDY COMPL PLOCEPLAIN SHOWN ON FIRM MAP NUMBERS FOR SITE AGREAGES OF CONSTRUCTION WIFLOODPLAN. DEBISN CERTIFICATION

THE DRAWINGS, CONSTRUCTION HOTER, AND REFERENCE DIAGRAMS

ANTERIO RESOUNCES WILL OBTAIN AN ENCROAD-MENT PERMIT JUM-1003 PROM THE WEST VIRGINIA DEPARTMENT OF TRANSPORTATION, DIVISION OF HIGHWAYS,

